

# PRH74



## FEATURES 特点

- \* Excellent solderability and high heat resistance  
良好的可焊性和高耐热性

## APPLICATION 用途

- \* DC / DC 转换器

## MEASURING FREQUENCY 测试频率

- \* 100KHz 0.3V

## Shapes And Dimensions 外形及尺寸示意图



## Electrical Characteristics 电气性能

Type 型號	Indicate 表示	Inductance 電感值	D.C.R(Max) 直流電阻(mΩ)	Rated Current(Max) 額定電流(A)
PRH74-4R7	4R7	4.7μH±30%	26m(19m)	2.80
PRH74-120	120	12μH±30%	58m(44m)	1.71
PRH74-150	150	15μH±30%	81m(62m)	1.47
PRH74-180	180	18μH±30%	91m(70m)	1.31
PRH74-220	220	22μH±30%	0.11(77m)	1.23
PRH74-270	270	27μH±30%	0.15(0.12)	1.12
PRH74-330	330	33μH±30%	0.17(0.13)	0.96
PRH74-390	390	39μH±30%	0.23(0.18)	0.91
PRH74-470	470	47μH±30%	0.26(0.20)	0.88
PRH74-560	560	56μH±30%	0.35(0.27)	0.75
PRH74-680	680	68μH±30%	0.38(0.30)	0.69
PRH74-820	820	82μH±30%	0.43(0.33)	0.61
PRH74-101	101	100μH±30%	0.61(0.47)	0.60
PRH74-121	121	120μH±30%	0.66(0.51)	0.52
PRH74-151	151	150μH±30%	0.88(0.68)	0.46
PRH74-181	181	180μH±30%	0.98(0.76)	0.42
PRH74-221	221	220μH±30%	1.17(0.90)	0.36
PRH74-271	271	270μH±30%	1.64(1.32)	0.34
PRH74-331	331	330μH±30%	1.86(1.49)	0.32
PRH74-391	391	390μH±30%	2.85(2.28)	0.29
PRH74-471	471	470μH±30%	3.01(2.41)	0.26
PRH74-561	561	560μH±30%	3.62(2.89)	0.23
PRH74-681	681	680μH±30%	4.63(3.71)	0.22
PRH74-821	821	820μH±30%	5.20(4.16)	0.20
PRH74-102	102	1000μH±30%	6.00(4.80)	0.18

\* SPQ:1000PCS/REEL

The sample parameters are based on actual measured values